

ViewSonic®

## PJ350 Projector



## LiteBird™ Series

### PJ350 3.3-pound micro-portable projector.

Feel confident walking into any presentation setting with the micro-portable ViewSonic PJ350. Weighing in at just 3.3 pounds, this high-performance projector is the ultimate choice for traveling business professionals who demand excellent image quality in a lightweight, easy-to-carry package. With XGA resolution, high brightness and contrast as well as full functionality this projector will make it easy for you to present a positive image anytime, anywhere. With Digital Keystone Correction, picture-in-picture and zoom functions this projector is flexible for any presentation setting. In addition, it is capable of displaying DVI-I and HDTV signals as well as other video and data sources.

- **Ultra lightweight 3.3 lb micro-portable projector**  
Packs a lot of power in only 3.3 pounds.
- **Professional level 1100 lumens**  
Get clear, bright presentations in any setting.
- **True 1024 x 768 XGA resolution**  
Produces clear, crisp images.
- **Easy set-up and auto tuning**  
One-touch setup button for fast, easy sync and sharp focus.
- **Digital Light Processing (DLP™) by Texas Instruments®**  
Excellent color contrast, bright, vivid images and excellent video quality.
- **PersonalTheater™ projection for movies, sports and more**
- **Supports HDTV and DVI-I signals**
- **Digital Keystone Correction**  
Squares up the picture when projecting at an angle.
- **Wireless remote control**  
Gives you total control, flexibility and convenience.



**ViewSonic®**  
*See the difference!®*



# ViewSonic PJ350

## PROJECTOR

### MICRO-PORTABLE LITEBIRDPROJECTOR

DLP	<b>Type</b>	TI 0.7" XGADLP™
	<b>Pixel Format</b>	1024 Horizontal x 768 Vertical
	<b>Lens</b>	Manual zoom/focus F(2.2-2.4) f(28.51mm-14.21mm)
DISPLAY	<b>Size</b>	20" to 300" (measured diagonally)
	<b>Focus Distance</b>	1.0 to 12.0M
	<b>Lamp</b>	130W OSRAM P-VIP, 1500 hour rating
	<b>Brightness</b>	1100 Lumens
AUDIO	<b>Contrast Ratio</b>	500:1
	<b>Speakers</b>	40mm (W) x 28.2mm (H) x 11mm (D), Oval x1
	<b>Power</b>	2W (at 1KHz/0.5% THD)
INPUT SIGNAL	<b>Video</b>	RGB analog, NTSC M, NTSC 4.43, PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, L), HDTV
	<b>Sync Frequency</b>	Separated, Composite and Sync on Green (SOG) F <sub>H</sub> : 15-100kHz; F <sub>V</sub> : 43-120Hz
COMPATIBILITY	<b>PC</b>	Analog: from VGA up to SXGA Digital: from VGA up to XGA
	<b>Mac**</b>	Analog: up to SXGA (may require Mac Adapter) Digital: up to XGA (may require Mac Adapter)
CONNECTOR	<b>RGB</b>	15-pin HD, D-sub (loop through – output only)
	<b>DVI</b>	High density 29-pin DVI-I
	<b>Video</b>	RCA
	<b>S-Video</b>	SVHS DIN Connector
	<b>Audio</b>	3.5mm Mini Stereo Plug
POWER	<b>Remote Mouse In</b>	Din 8-pin
	<b>Voltage</b>	100-240 VAC, 50-60Hz (universal)
USER CONTROLS	<b>Consumption</b>	180W (typ)
	<b>Physical</b>	Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -)
	<b>Remote</b>	Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu
OPER. COND.	<b>OSD</b>	Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only), sharpness (video only), color (video only), aspect ratio, tracking, frequency, horizontal position, vertical position, signal type (RGB, component, HDTV), reset]
	<b>Temperature</b>	Language
	<b>Humidity</b>	Audio [volume, bass, treble, mute, stereo/mono]
	<b>Physical</b>	Projection [front, rear, front ceiling, rear ceiling] Lamp [lamp reminder, lamp reset]
	<b>Net</b>	
DIMENSIONS		223mm (W) x 175mm (D) x 52mm (H) (8.8" x 6.9" x 2.1")
WEIGHT		1.5kg (3.3 lbs.)
REGULATIONS		UL, FCC-B, c-UL, FDA, CE, TUV/GS, CB, BSMI, VCCI, PSC PCT
WARRANTY		Two-year limited on parts and labor. 90-day on lamp.
OTHER		Remote range = 5m, front and rear projection, 10 user modes

- User-replaceable extended-life lamp

Extended lamp life up to 1,500 hours.

- Soft carry case included for easy travel

- Industry-leading 24/7 customer support

- Optional accessories

Executive carrying case

Replacement lamp

Ceiling/wall mount kit

Extended warranty

48-hour Express Exchange®

**ViewSonic®**  
*See The Difference!™*

#### Headquarters:

381 Brea Canyon Road, Walnut,

CA 91789, U.S.A.

Tel: 1-909-869-7976 800-888-8583

Fax: 1-909-869-7958

Internet: <http://www.viewsonic.com>

#### Asia Pacific Sales:

9F, No. 192, Lien Chen Road, Chung Ho,

Taipei, Taiwan, R.O.C.

Tel: 886-2-2246-3456

Fax: 886-2-8242-3666

E-mail: [vsitech@viewsonic.com.tw](mailto:vsitech@viewsonic.com.tw)



**ViewSonic®**  
*See the difference!®*

Copyright © 1999, ViewSonic Corporation. All rights reserved. Corporate names and trademarks stated herein are the property of their respective companies.

Specifications subject to change without notice. The EPA only promotes energy efficiency and does not endorse any particular company or product.

Microsoft, Windows, Windows NT and the Windows logo are the registered trademarks of Microsoft Corporation in the United States and other countries.

BVE0106PJ350 2K